

## **Pipings & devices Specifications**

<b>Item No</b>	<b>Description</b>	<b>Quantity</b>
<b>2.1</b>	PVC 1" HI SCH 40	
<b>2.2</b>	PVC 2" HI SCH 40	
<b>2.3</b>	PVC 3" HI SCH 40	
<b>2.4</b>	PVC 1"1/4 HI SCH 40	
<b>2.5</b>	EMT 1"	
<b>2.6</b>	EMT 2"	
<b>2.7</b>	EMT 3"	
<b>2.8</b>	EMT 1"1/4	
<b>2.9</b>	Safety Switch 200 amps	
<b>2.10</b>	Safety Switch 400 amps	
<b>2.11</b>	Safety switch 600 Amps/ 3 poles ( fusibles 600 Amps inclus)	
<b>2.12</b>	Double Throw Switch 600 Amps	
<b>2.13</b>	Switchboard 800 Amps/ 3 poles	
<b>2.14</b>	Load center 12 spaces 125 AMPS, 120/208Y	
<b>2.15</b>	Load center 20 spaces 125 AMPS, 120/208Y	
<b>2.16</b>	#2 Bare Copper Wire	
<b>2.17</b>	PLUGS and SCREWS	

### **General requirements for :**

□